



printlux no-lite 250

Technical Information

➤ **General information**

- 250 µm, polyester compound
- glossy finish
- 100 % opaque, blocks all background light
- dimensionally stable
- front side bright white, reverse side grey
- top quality InkJet-coating

➤ **Areas of application**


- suitable for thermal InkJet printers
- designed for dye inks
- for indoor use
- ideal for panel production (Roll-Up, Pop-Up, etc.)

➤ **Processing & Handling**

- please notice Handling- and Storage Conditions in our catalog or visit our homepage www.neschen.de
- to avoid fingerprints, protective gloves are best to be worn while handling
- storage is best to be done in the original case

➤ **Advantages / Special Features**

- photorealistic print quality
- high colour brilliance
- quick drying
- ICC-profiles available
- for more information see the latest Neschen compatibility list (at www.neschen.de)



printlux no-lite 250

Technical Information

➤ Technical Data

➤ Carrier:

Film type:	Polyester-film, opaque, white, reverse side grey		
Thickness [µm]:	ca. 240 approx. 9,4 mil		
Weight [g/m²]:	ca. 350		
Gloss [Scale units]:	> 85	Reflektometer Dr. Lange, 60° angle	

➤ Others:

Handling/Storage Conditions:	18° to 25°C / 60° to 80° F; 40 to 65% relative humidity		
Shelf Life [Years]:	3		
Temperature Stability:	-30 to +50°C	-22 to +122°F	affixed to aluminium
Humid Climate Stability: [change/no change]	no change	2 weeks affixed to aluminium at 40°C (104°F) and 95% rel. humidity	

All tests were performed in accordance with 23/50-2, DIN 50014.