

solvoprint wallpaper linen P

Technical Information

➤ General Information

- ca. 295 g/m² heavy PVC coated paper
- Inkjet printable wallpaper with textured surface
- opaque appearance
- flame retardency treatment / **B1 test certificate**

➤ Areas of Application

- suitable for eco solvent, real solvent and UV curable ink systems
- very hard-wearing, printable wallpaper for creative wall design
- suitable for indoor application
- application without laminating is possible
- more durability potential with liquid lamination

➤ Processing & Handling

- for adhesion we recommend P.V.A.C. dispersion glue (e.g. Ovalit T from Henkel)
- processing is possible with useful tools
- no special knowledge necessary
- for further handling please inform at the down-load area www.neschen.de

➤ Advantages / Special Features

- bright colours with high brilliance and very good print quality due to special PVC coating
- good scratch resistance after complete drying
- quick drying with normal ink load
- ideal for creating customised interior design
- for more information see the latest Neschen compatibility list (at www.neschen.de)

solvoprint wallpaper linen P

Technical Information

➤ Technical Data

➤ Carrier:

carrier material:	Paper with PVC coating
thickness [µm]:	ca. 410 +/- 40
weight [g/m²]:	ca. 295 +/- 15
gloss level:	matt, textured surface
whiteness: [Lab]	L* 95,75 a* 0,10 b* -1,10
Stiffness md (mN) : 20°-15mm	MD 150 +/- 40 mN / CD 95 +/- 15 mN

➤ More informations:

storage conditions:	original boxed at 5 – 40°C / 40 to 100°F / RH: 30% - 90%
material durability [months]:	12 months
flame retardency treatment:	B1 test certificate

All tests were performed in accordance with 23/50-2, DIN 50014.