

# solvotex art canvas

## Technical Information

### ➤ **General information**

- Polyester/cotton fabric
- approx. 340 g/ m<sup>2</sup> incl. Inkjet coating
- heavy linen weave
- white

### ➤ **Areas of application**

- printable with solvent, eco solvent Ink and as well as with UV-curable inks
- for all kinds of application (indoor and outdoor)
- especially for Displays, Banners, Exhibitions, Graphic arts, theatre decorations etc.

### ➤ **Processing & Handling**

- for further handling and storage recommendations please refer to the latest product catalogue or visit our homepage under [www.neschen.com](http://www.neschen.com)
- print slowly
- to avoid fingerprints, protective gloves are recommended to be worn while handling
- to prevent problems after processing / laminating, make sure all prints have been allowed sufficient time to thoroughly dry (dry time of 12 hours to be assured)

### ➤ **Advantages / Special Features**

- highest brilliance
- photorealistic print quality
- printable with solvent, eco solvent Ink and as well as with UV-curable inks
- quick drying time
- high color aplikation is possible
- good plain weave
- strain on an frame

# solvotex art canvas

## Technical Information

### ➤ Technical Data

#### ➤ Carrier:

<b>Material:</b>	Polyester		
<b>Weight [g/m<sup>2</sup>]:</b>	approx: 340		
<b>Thickness [µm]:</b>	approx.: 395 / approx. 15,5 mil		
<b>Tear force [N/15mm] ():</b>	warp / weft	173 / 182	DIN 53455
<b>Elongation at tear[%]:</b>	warp / weft	11 / 15	
<b>Tear resistance [N/mm<sup>2</sup>] ():</b>	warp / weft	29 / 31	DIN 53455

#### ➤ Others:

<b>Shelf life [years]:</b>	2 years after the date of production
<b>Handling/storage conditions:</b>	-20° to + 80°C (5° to 170 °F)

All tests were performed in accordance with 23/50-2, DIN 50014.