

solvoprint easy panel 310 B1 CA

Technical Information

➤ General Information

- CA version with improved coating
- ca. 310 µm rigid-PVC as carrier
- matt, special inkjet coating for solvent-and UV curable inkjet printers
- good stiffness
- opaque appearance
- flame retardency treatment / **B1 test certificate** DIN 4102-1

➤ Areas of Application

- suitable for eco solvent, real solvent and UV curable ink systems
- strong, ideal for Pop Up systems, especially for stronger curved end caps
- suitable for indoor and for short term outdoor
- application whitout laminat is possible

➤ Processing & Handling

- to avoid fingerprints, usage of cotton gloves is recommended
- for protective purpose usage of Neschen Protective Laminates is recommended (ensure adaequate drying before lamination) – drying time of min. 12 hours is recommended.
- please notice Handling- and Storage Conditions in our catalogue or visit our homepage www.neschen.de
- storage is best to be done in the original case
- we recommend to use heat-settings of not more than 35° celsius

➤ Advantages / Special Features

- very good colour reproduction and photorealistic print quality
- quick drying with normal ink load
- multi-purpose but especially for Roll Up - and other display systems
- part of Neschen´s Display Graphics Solutions (DGS)
- for more information see the latest Neschen compatibility list (at www.neschen.de)

solvoprint easy panel 310 B1 CA

Technical Information

➤ **Technical Data**

➤ **Carrier:**

| | |
|----------------------------------|------------------------|
| carrier material: | Rigid-PVC |
| thickness [µm]: | ca. 310 ± 7% |
| weight [g/m²]: | ca. 445 ± 7% |
| gloss level: | matt coating |
| whiteness: [Lab] | L* 95,0 a* 0,0 b* -2,0 |

➤ **More informations:**

| | |
|--------------------------------------|--|
| storage conditions: | original boxed at 10 – 35°C |
| material durability [months]: | 18 months |
| temperature resistance: | shrinkage: long = max. -8% transversal = max. ± 2% |
| flammability: | B1 certificate DIN 4102-1 |