

solvotex artist premium light S

Technical Information

➤ **General information**

- 100 % polyester fabric
- approx. 200 g/ m² incl. Inkjet coating
- light linen weave
- white

➤ **Areas of application**

- printable with solvent, eco solvent as well as with UV-curable inks
- for all kinds of application (indoor and outdoor)
- especially for rotating billboards, displays, banners, exhibitions, graphic arts, theatre decorations etc.

➤ **Processing & Handling**

- for further handling and storage recommendations please refer to the latest product catalogue or visit our homepage under www.neschen.com
- to avoid fingerprints, protective gloves are recommended to be worn while handling
- to prevent problems after processing / laminating, make sure all prints have been allowed sufficient time to thoroughly dry (dry time of 12 hours to be assured)
- expected outdoor durability up to 6 months (storm damages an other environmental influences excepted)

➤ **Advantages / Special Features**

- highest brilliance
- fast drying time
- high colour resolution is possible
- suitable for back-lighting
- good plain weave

solvotex artist premium light S

Technical Information

➤ **Technical Data**

➤ **Carrier:**

Material:	Polyester		
Weight [g/m²]:	approx: 200		
Thickness [µm]:	approx: 230 / approx. 9 mil		
Breaking force[N/15mm]:	warp / weft	470 / 362	DIN 53455
Elongation at tear[%]:	warp / weft	41 / 35	
Tear resistance [N/mm²]:	warp / weft	133 / 102	DIN 53455

➤ **Others:**

Shelf life [years]:	2 years after the production date
Handling/storage conditions:	-20° to + 80°C (5° to 170 °F)
flammability:	DIN 4102 B1, NFPA - 701

All tests were performed in accordance with 23/50-2, DIN 50014.