

solvotex artist banner heavy

Technical Information

➤ **General information**

- 100 % polyester fabric
- ca 280 g/m² incl. Inkjet coating
- linen weave
- white

➤ **Areas of application**

- printable with solvent- and eco solvent Inks
- for all kinds of application (indoor and outdoor)
- especially for Display Panels, Banners, Exhibitions, Graphic arts, theatre decorations etc.

➤ **Processing & Handling**

- for further handling and storage recommendations please refer to the latest product catalogue or visit our homepage under www.neschen.com
- print slowly
- to avoid fingerprints, protective gloves are recommended to be worn while handling
- to prevent problems after processing / laminating, make sure all prints have been allowed sufficient time to thoroughly dry (dry time of 12 hours to be assured)
- expected outdoor durability up to 6 months (storm damages and other environmental influences excepted)

➤ **Advantages / Special Features**

- highest brilliance
- fast drying time
- can be used outdoors and indoors
- high color application is possible
- possible for investigation
- good plain weave
- strain on an frame

solvotex artist banner heavy

Technical Information

➤ **Technical Data**

➤ **Carrier:**

Material:	Polyester		
Weight [g/m²]:	approx: 280		
Thickness [µm]:	approx: 390 / approx. 15,3 mil		
Tear force [N/15mm]:	warp / weft	453 / 489	DIN 53455
Elongation at tear[%]:	warp / weft	54 / 73	
Tear resistance [N/mm²]:	warp / weft	77 / 81	DIN 53455

➤ **Others:**

Shelf life [years]:	2 years after the production date
Handling/storage conditions:	-20° to + 80°C (5° to 170 °F)
flammability:	DIN 4102 B1, NFPA - 701

All tests were performed in accordance with 23/50-2, DIN 50014.