



printex canvas 280

Technical Information

➤ General information

- 280 g/m² true linen fabric
- front side white, reverse side natural
- topgrade InkJet-coating
- glossy finish

➤ Areas of application

- suitable for thermal printers
- designed for dye inks
- ideal material for perfect art reproduction
- suitable for mounting on a frame

➤ Processing & Handling

- please notice Handling- and Storage Conditions in our catalog or visit our homepage www.neschen.de
- to avoid fingerprints or stains, protective gloves should be worn during handling
- storage is best to be done in the original case

➤ Advantages / Special Features

- photo quality printing
- full, rich colors
- quick drying
- ICC-profiles available
- for more information see the latest Neschen compatibility list (at www.neschen.de)

➤ Technical Data

➤ Carrier:

Film type:	linen fabric, white, opaque, coated
Thickness [µm]:	ca. 410 approx. 16 mil
Weight [g/m²]:	ca. 280

➤ Others:

Handling/Storage Conditions:	18° to 25°C / 60° to 80° F; 40 to 65% relative humidity		
Shelf Life [Years]:	3		
Temperature Stability:	-10 to +50°C	+14 to +122°F	affixed to aluminium
Humid Climate Stability: [change/no change]	no change	2 weeks affixed to aluminium at 40°C (104°F) and 95% rel. humidity	

All tests were performed in accordance with 23/50-2, DIN 50014.

