



# printlux paper 120

## Technical Information

### ➤ General information

- 120 g/m<sup>2</sup> coated paper
- bright white InkJet-coating
- matt finish

### ➤ Areas of application


- suitable for thermal and piezo printers
- designed for dye pigmented, oil-based and light-solvent inks
- for indoor application
- can be cold-laminated

### ➤ Processing & Handling

- please notice Handling- and Storage Conditions in our catalog or visit our homepage [www.neschen.de](http://www.neschen.de)
- to avoid fingerprints or stains, protective gloves should be worn during handling
- storage is best to be done in the original case

### ➤ Advantages / Special Features

- poster quality printing
- brilliant colors
- high resolution printing
- quick drying
- ICC-profiles available
- for more information see the latest Neschen compatibility list ( at [www.neschen.de](http://www.neschen.de) )



# printlux paper 120

## Technical Information

### ➤ Technical Data

#### ➤ Carrier:

<b>Film type:</b>	special InkJet-paper, white, coated
<b>Thickness [µm]:</b>	150 ± 10 approx. 6 mil
<b>Weight [g/m<sup>2</sup>]:</b>	120 ± 10

#### ➤ Others:

<b>Handling/Storage Conditions:</b>	18° to 25°C / 60° to 80° F; 40 to 65% relative humidity		
<b>Shelf Life [Years]:</b>	3		
<b>Temperature Stability:</b>	-30 to +50°C	-22 to +122°F	affixed to aluminium
<b>Humid Climate Stability: [change/no change]</b>	no change	2 weeks affixed to aluminium at 40°C (104°F) and 95% rel. humidity	

All tests were performed in accordance with 23/50-2, DIN 50014.

