

solvoprint wallpaper classic P

Technical Information

➤ General Information

- ca. 295 g/m² heavy PVC coated paper
- Inkjet printable wallpaper with textured surface
- opaque appearance
- flame retardency treatment / **B1 test certificate**

➤ Areas of Application

- suitable for eco solvent, real solvent and UV curable ink systems
- very hard-wearing, printable wallpaper for creative wall design
- suitable for indoor application
- application without laminating is possible
- more durability potential with liquid lamination

➤ Processing & Handling

- for adhesion we recommend P.V.A.C. dispersion glue (e.g. "**Ovalit T**" from Henkel)
- processing is possible with useful tools
- no special knowledge necessary

➤ Advantages / Special Features

- bright colours with high brilliance and very good print quality due to special PVC coating
- good scratch resistance after complete drying
- quick drying with normal ink load
- ideal for creating customised interior design
- for more information see the latest Neschen compatibility list (at www.neschen.de)

solvoprint wallpaper classic P

Technical Information

➤ Technical Data

➤ Carrier:

carrier material:	paper with PVC coating	
thickness [µm]:	ca. 380 ± 40	approx. 15 mil
weight [g/m²]:	ca. 295 ± 15	
gloss level [85°]:	0,40 ± 0,15	
whiteness: [Lab]	L* 95,75; ± 0,50 a* 0,10 ± 0,50 b* -1,10 ± 0,70; DE 100	
opacity:	> 99,0	
tensile strength [N/1,5cm]	MD: ≥ 40 / CD: ≥ 13	
elongation at break [%]	MD: ≥ 1,0 / CD: ≥ 2,4	
Stiffness md (mN) : 20°-15mm	MD 170 ± 40 / CD 105 ± 20	

➤ More informations:

storage conditions:	original boxed at 5 – 40°C / RH: 30% - 90% - keep dry, indoor
material durability [years]:	1
flame retardency treatment:	B1 test certificate

All tests were performed in accordance with 23/50-2, DIN 50014.